



NO	NAME OF PARTS	QTY	MATERIALS	SPECIFICATIONS
1	轴		CF8M	
2	轴套		316	
3	密封环(密封环)		CF8M	
4	轴套		316	
5	轴套		316	
6	轴套		CF8M	
7	密封环		G.P/316	

DN	L	D	D1	D2	b	f	Z-ød
200	480	342.9	298.5	269.7	28.4	1.6	8-ø22.4
150	380	279.4	241.3	215.9	25.4	1.6	8-ø22.4
125	335	254	215.9	185.7	24	1.6	8-ø22.4
100	300	228.6	190.5	157.2	24	1.6	8-ø19.1
80	275	190.5	152.4	127	19	1.6	4-ø19.1
65	250	177.8	139.7	104.6	18	1.6	4-ø19.1
50	215	152.4	120.7	91.9	16	1.6	4-ø19.1
40	200	127	98.6	73.15	14	1.6	4-ø15.7
32	180	117.3	88.9	63.5	12.7	1.6	4-ø15.7
25	160	108	79.25	50.8	12	1.6	4-ø15.7
20	150	98.6	69.85	42.9	12	1.6	4-ø15.7
15	125	88.9	60.45	35	11.2	1.6	4-ø15.7

TEST PRESSURE	(class)150LB		SHELL		SEAT	
	HYDROSTATIC	PSI	3.0	MPa	PSI	2.2
	AIR	PSI	0.6	MPa	PSI	0.6
	TEMPERATURE		-29~425℃		MEDIAL	

STANDARD	FACE TO FACE OR END TO END	
	END CONNECTION	ANSI 150
	WALL THICKNESS	HG/T 21637-1991
	VALVES TEST	压力容器检验规范

150LB

DATE APPD		DRAWING NO			
APPD BY		CF8M			
CHKD BY					
DSGND BY					
DRAWN BY					
			MARK	DATE	BY